Checkpoint ILS Preferences

Preferences

- Patrons
- Items
- Circulation
- Codes
- Circulation Groups
- Z39.50
- Sounds
- Setup
- Services
- SIS Integration
- Advanced Bookings

How helpful was this page?

Unknown macro: 'rate'

Tell us what we can improve.

Related Blog Posts

Blog Posts

- Blog: Winter storms–recompute due dates created by
  Bethany Brown
  Jan 23, 2024
  Alexandria
- Blog: Cleaning up the grade table–Authority Control created by
  Bethany Brown
  Apr 26, 2023
  Alexandria
- Blog: Make a calendar just for the senior class! created by
  Bethany Brown
  Aug 02, 2022
  Alexandria
- Blog: When does an overdue item become lost? created by
  Bethany Brown
  Mar 15, 2022
  Alexandria
- Blog: Setting rules–Patron Policy Preferences created by
  Bethany Brown
  Mar 08, 2022
  Alexandria
- Blog: Seeing double (barcodes) on patrons and items? created by
  Bethany Brown
  Feb 23, 2022
  Alexandria
- Blog: Automatic email notices... What are you waiting for? created by
  Bethany Brown
  Nov 17, 2021
  Alexandria
- Blog: Winter (break) is coming! Are your period due dates set? created by
  Bethany Brown
  Oct 20, 2021
  Alexandria

Save as PDF

Checkpoint

⚠ Checkpoint ILS is being discontinued due to a lack of interest.

Checkpoint ILS Preferences

Preferences > Setup > Checkpoint ILS

⚠ SYSTEM Preference

SHARED with Textbook Tracker

Configure these settings if you are using the **Checkpoint ILS** (**I**ntelligent **L**ibrary **S**ystem) security system to enhance your SIP2 protocol. Remember, this should only be enabled if Checkpoint's SIP2 hardware is in use (SIP2 hardware is not interchangeable between manufacturers). The technician installing your Checkpoint system should be able to configure these settings for you.

Make sure all **SIP2** settings are correct and that you have an FTP server running on the same machine as your Alexandria Data Station. The ILS server will place an inventory file on your Data Station. If you are not running an FTP server on your Data Station, the inventory file will need to be placed manually.

⊘ **Checkpoint ILS** settings are available to those running a **Centralized Catalog** or a **Distributed Catalog**, regardless if it's under a Controller or an independently operated Data Station. These settings *also* appear for those benefiting from our **Cloud-Hosted** services. *Note*: In a Centralized Catalog, these settings will apply to *all* sites.

Settings

Enable Checkpoint ILS

This box should only be enabled if Checkpoint's SIP2 hardware is in use.

Inventory File

Enter the directory for the ILS server to place the inventory file it creates. If the ILS server has not yet created an inventory file, an empty file (of the same name and path) should be created.

Synchronization Folder

As part of the Checkpoint ILS system Alexandria will create a synchronization file, co_cache.txt, that contains a list of barcodes for each item that is currently outside of the library (checked out). This file is placed inside the synchronization folder you specify here.

ILS Server Address

Enter the web address of the ILS FTP server you're trying to connect to. An FTP address looks a lot like an HTTP (website) or IP address, except it uses the prefix *ftp://* instead of *http://* and can be any combination of letters and numbers.

ILS FTP Path

Checkpoint ILS Preferences

Enter the directory path of the ILS FTP server where Alexandria will send its data. If you get an error message when trying to connect, be sure to check your FTP path. Default is / .

FTP Username

Enter the username used to access the ILS FTP server.

FTP User Password

Enter the password used to access the ILS FTP server.