

Search Strings

Search

How helpful was this page?



Unknown macro: 'rate'

[Tell us what we can improve.](#)

Related Blog Posts

Blog Posts

- Blog: [Site-specific eBooks](#) created by [Bethany Brown](#)
Jan 10, 2024
[Alexandria](#)
- Blog: [Builder: customize your search](#) created by [Bethany Brown](#)
Nov 21, 2023
[Alexandria](#)
- Blog: [Items: a few things you may not know...](#) created by [Bethany Brown](#)
Apr 12, 2023
[Alexandria](#)
- Blog: [Searching by Subject](#) created by [Bethany Brown](#)
Nov 16, 2022
[Alexandria](#)
- Blog: [Level up your searching](#) created by [Bethany Brown](#)
Sep 21, 2022
[Alexandria](#)
- Blog: [Using Copy Location & Copy Shelving](#) created by [Bethany Brown](#)
Aug 24, 2022
[Alexandria](#)
- Blog: [¿Hablas español? - Filter search results by language](#) created by [Bethany Brown](#)
Aug 16, 2022
[Alexandria](#)
- Blog: [Top 5 tips of 2021!](#) created by [Bethany Brown](#)
Dec 29, 2021
[Alexandria](#)
- Blog: [Search smarter!—Combine search results](#) created by [Bethany Brown](#)
Oct 13, 2021
[Alexandria](#)
- Blog: [New Inventory—Using Search Strings](#) created by [Bethany Brown](#)
Sep 29, 2021
[Alexandria](#)

[Save as PDF](#)



Search Strings

Last Updated: \$action.dateFormatter.formatDateTime(\$content.getLastModificationDate())



About



This information (all tabs) has been moved to <https://support.goalexandria.com/researcher/search/search-strings/>

What is a Search String?

A search string is a line of plain-text comprised of types, values, and operators that are easily combined to form a search query. For example, `((smart::cat)&&(smart::dog))` would search for items in your collection that contain both cats and dogs. Alexandria uses predefined syntax to interpret such strings, allowing you to compose your own search strings capable of performing complex queries against your database. These can be used directly in the search interface or as the basis for [Explore buttons](#), [slideshows](#), links and more.

Search strings must be enclosed within double-parentheses `((queryType::searchValue))`. Alexandria will locate the first and last parentheses and evaluate everything between from left-to-right. If there are "nested" parentheses, they will be evaluated first. Use parentheses within the string to differentiate multiple expressions, like this: `((queryType::searchValue) && (queryType::searchValue))`

Create a Search String

You can build a search string from scratch by manually combining various queries. However, we recommend starting with a pre-built string created in Search:

1. In **Search**, [set up your search](#). This could include defining a Search Type; typing a term into the search bar; adding Study Programs, Medium, or Genre filters; or using [Advanced Search](#) for more complex searches.



You can use the Study Programs, Medium, or Genre search filters in conjunction with Advanced Search. However, Alexandria will filter results by those selectors first before filtering results by the Advanced Search selections.

2. Press **Enter** on your keyboard.
3. Click on the **Share** button in the [control bar](#).
4. Click on the search string to copy it to your clipboard.

If necessary, you can then paste the string into a text editor and modify or add to the queries manually (see [Query Types & Values](#) and [Separators & Operators](#)).

Once you're done customizing your search string, add it to an [Explore button](#), [slideshow](#), [bulletin](#), or more for others to view or use.

Query Types & Values



This information (all tabs) has been moved to <https://support.goalexandria.com/researcher/search/search-strings/>

Query Types & Values

Query Type	Search Value	Example	Usage Notes
accession	Accession Date (DateTime)	(accession::201611170000) (accession::201611170000--201612170000) (accession::#201611150000)	Searches by Accession Date in YYYYMMDDHHMM. Use "::#" as the separator to make this a begins with search.

author	Author Names (Text)	((author::rowling)) ((author::#rowling) && (author::#j k))	Searches fields: Personal Name—100a, 100q, 700a, 700q. Corporate Names—110a, 710a. Meeting name—111a, 711a. Use “::#” as the separator to make this an exact phrase search.
awards	Awards Notes (Text)	((awards::ala) && (awards::notable) && (awards::books)) ((awards::#caldecott) && (awards::#honor) && (awards::#book))	Searches field 586a. Use “::#” as the separator to make this a near term search.
bibliographic	Bibliographic Term (Text)	((bibliographic::whitestone) && (bibliographic::publishers))	Searches field 653a. Use “::#” as the separator to make this a near term search.
curriculum	Curriculum Term (Text)	((curriculum::geography) && (curriculum::212))	Searches field 658a. Use “::#” as the separator to make this a near term search.
electronic	Title Policy (Numeric Value, 0 or 1)	((electronic::1))	Setting ((electronic::1)) searches for items with an electronic resource policy only.
genre	Genre Term (Text)	((genre::science) && (genre::fiction)) ((genre::war) && (genre::stories)) ((genre::dystopians))	Searches field 655a. Ignores the “#” (if used) in the separator.
hidetitle	Title Attribute (Numeric Value, 0 or 1)	((hidetitle::1))	Setting ((hidetitle::1)) overrides the “Hide Title” settings and causes all titles to be displayed.
interest	Interest Term (Text)	((interest::mg))	Searches field 521a. Use “::#” as the separator to make this an exact match search.
ISBN	ISBN (Numeric Value)	((isbn::0760712107)) ((isbn::0439064864))	Searches field 020a. Ignores the “#” (if used) in the separator.
ISSN	ISSN (Numeric Value)	((issn::0689849974))	Searches field 022a. Ignores the “#” (if used) in the separator.
language	Language (Text)	((language::eng)) ((language::german))	Searches subfields: Language Code—41a Uniform Title—130l, 730l Language Note—546a. Use “::#” as the separator to make this an exact match search.
LCCN	LCCN (Numeric Value)	((lcn::2003002086))	Searches field 010a. Ignores the “#” (if used) in the separator.
link	Link Description (Text)	((link::mackinvia))	Searches field 856_y.
medium	Medium Type (Text)	((medium::book)) ((medium::text--unmediated--volume))	Searches fields: Title Statement—245h Content, Media, Carrier Type—336a, 337a, 338a Use “::#” as the separator to make this a near term search.

notes	Note (Text)	((notes::ships))	Searches fields: Content Notes—505a General Notes—500a Summary Notes—520a Use "::#" as the separator to make this a near term search.
popularity	Popularity (Text)	((popularity::90)) ((popularity::70--90))	((popularity::90)) will search for all items with a popularity score of 90% or above Use "::#" as the separator to search below the popularity number for weeding purposes.
pubyear	Pubyear (Text)	((pubyear::1996)) ((pubyear::1950--1955))	Searches fields: Publication Year—264c Use "::#" as the separator to make this a begins with search.
rating	Ratings, x' 10 (Numeric Value)	((rating::40)) ((rating::50)) ((rating::40--50))	Exactly 4 Stars Exactly 5 Stars Range, 4 through 5 Stars
savedlist	GUID (GUID)	((savedlist::5C8E874133AF4058B5527AC5F6B57E63)) ((savedlist::0D4E6E52E1444A74BAE4A3E792AA4527))	Returns all titles in a specified saved list. Do not combine with other types or used with multiple operators. Ignores the "#" (if used) in the separator. Saved List GUIDs are found in URLs generated when clicking Share ("").
series	Series Title /Statement (Text)	((series::harry) && (series::potter)) ((series::boxcar) && (series::children) && (series::mysteries)) ((series::hunger) && (series::games) && (series::trilogy))	Searches fields: Series Statement—490a Series Uniform Title—830a. Use "::#" as the separator to make this an exact match search.
smart	Relevancy Ranked Algorithm (Text)	((smart::harry potter)) ((smart::suzanne collins)) ((smart::mystery))	Searches on a multitude of fields and orders the results based on a proprietary weighting algorithm. A Smart Search should be used wherever you would normally specify a "keyword" type search.
studyintere stlevel	Study Program Interest Level (Text)	((studyinterestlevel::mg)) ((studyinterestlevel::ad))	Searches fields: Study Program Interest Level—526b Target Audience Note—521a, for Lexile Codes
studypoint count	Study Program Point Value, x's 10 (Numeric Value)	((studypointcount::15)) ((studypointcount::10--15))	Searches field 526d. Applies to Accelerated Reader and Reading Counts Only.
studyprogr amnameco de	Study Program Name Code (Numeric Value)	((studyprogramnamecode::1))	Searches by StudyProgram. Each Study Program is assigned a number: 1=Accelerated Reader 2=Reading Counts 3=Fountas and Pinnell 4=Guided Reading 5=Lexile.
studyreadi nglevel	Study Program Reading Level (Text)	(studyreadinglevel::01.10) (studyreadinglevel::00200) (studyreadinglevel::a) (studyreadinglevel::00500--02000)	Searches fields: Study Program Reading Level—526c, for Accelerated Reader and Reading Counts Target Audience Note—521a for all others. For AR/RC format as: 00.00 For Lexile format as: 00000 For others, format as: x

subjectwords	Subject (Text)	((subjectwords::united) && (subjectwords::states)) ((subjectwords::navy))	Searches fields: Personal Name—Fields 600a, 600x, 600y, 600z Corporate Name—610z, 610x, 610y, 610z Meeting Name—611a, 611x, 611y, 611z Uniform Title—630z, 630x, 650y, 650z Geographic Name—651z, 651x, 651y, 651z Use "::#" as the separator to make this a near term search.
title	Title (Text)	((title::the) && (title::mystery) && (title::of) && (title::the) && (title::stolen) && (title::boxcar)) ((title::#holes))	Searches fields: Translation of Title—242a, 242b Title Statement—245a, 245b Varying Form of Title—246a, 246b Former Title—247a, 247b Use "::#" as the separator to make this an exact phrase search. Uniform title 130a
titlecallnumber	Title Call Number (Text)	((titlecallnumber::793.7)) ((titlecallnumber::793.7 ta)) ((titlecallnumber::#793.7 tan))	Searches field 991a Use "::#" as the separator to make this a begins with search.
titlersn	RSN (Numeric Value)	((titlersn::4139))	Searches for a specific titlersn.
titlersns	RSN (Numeric Value)	((titlersns::nn,nn,nn))	A comma delimited list of title rsns (e.g. from temp lists).
Copy Query Types & Values			
copycallnumber	Copy Call Number (Text)	((copycallnumber::FIC)) ((copycallnumber::FIC EVE))	Searches field 852h Use "::#" as the separator to make this a begins with search.
copybarcode	Copy Barcode (Text)	((copybarcode::10456)) ((copybarcode::10456--10457))	Searches field 852p
Additional Centralized Catalog Query Types and Values			
sitecode	Site Code (Text)	((sitecode::ams))	The site code assigned by the librarian.
sitersn	RSN (Numeric Value)	((sitersn::5)) ((sitersn::3--5))	The sitersn is the location of a site within the database.
KNOCOPY	KNOCOPY (Text)	((smart::oz) && (sitersn::1) (site::KNOCOPY))	When used, KNOCOPY will return electronic items that have no copies. In other words, items that belong to the entire catalog rather than a specific site.
Non-Index Query Parameters			
numrecords	Numrecords (Numeric Value)	((numrecords::10))	Limits the number of items returned in a query. Has a max limit of 1000 no matter what number is entered.

Separators & Operators

Separators & Operators

Separators	Function
::	Use a double colon (::) as the separator between query types and search values.

::#	To perform a special "variant" for search values, use the separator of "::#". For example, ((series::#Harry Potter)) searches for an exact series match of "Harry Potter". The way that special variants are handled depends on the individual query type. Although it's always valid to include the #, it may be ignored in many cases.
-----	--

Operators	Function
&&	Performs the Boolean operator AND.
	Performs the Boolean operator OR.
&-	Performs the Boolean operator AND NOT.
--	Separate terms using two hyphens without spaces (--) to search for a range of results such as dates, ratings, or call numbers. For example: ((copycallnumber::FIC EVA--FIC EVE)).
" "	Enclosing words in quotation marks (" ") tells Alexandria to interpret the character sequence literally, and not as part of the normal search string syntax. For example, double-hyphens (--) in search strings are interpreted as a range. However, two hyphens also separate subfields in subject headings. Therefore, you must contain certain search phrases in quotations in order to get relevant results, such as ((subject::"Basketball -- Tournaments -- United States")).

Examples

Examples of Combined Types and/or Multiple Operators

Alexandria only accepts a maximum of ten expressions in a single search string.

General Title

```
((author::rowling) &- (title::harry))
((subjectwords::civil) && (subjectwords::war) && (medium::book))
```

Smart Search

```
((smart::harry potter) && (medium::book))
((smart::oz) && (medium::electronic) && (medium::resource))
```

Accession

```
((accession::#201501010000))
((accession::201501010000--201601010000))
```

Combined and Boolean Searches

```
((smart::animals) &- (smart::birds) || (smart::reptiles))
((series::graphic) && (series::novels) && (medium::electronic) || (medium::ebook))
```

Rating

```
((rating::40) && (medium::book))
((rating::30--50) && (author::king))
```

Study Programs

Accelerated Reader

```
((studyprogramnamecode::1))
((studyprogramnamecode::1) && (studyreadinglevel::03.00--03.50))
((studyprogramnamecode::1) && (studyreadinglevel::03.00--03.50) && (studypointcount::15--20))
```

Reading Counts

```
((studyprogramnamecode::2))
((studyprogramnamecode::2) && (studyreadinglevel::03.00--05.50))
((studyprogramnamecode::2) && (studyreadinglevel::03.00--05.50) && (studyinterestlevel::mg) && (studypointcount::15--20))
```

Fountas and Pinnell

```
((studyprogramnamecode::3))
((studyprogramnamecode::3) && (studyreadinglevel::D))
```

Guided Reading

```
((studyprogramnamecode::4))
((studyprogramnamecode::4) && (studyreadinglevel::D))
```

Lexile

((studyprogramnamecode::5))

((studyprogramnamecode::5) && (studyreadinglevel::00300--00500))

((studyprogramnamecode::5) && (studyreadinglevel::00100--00200) && (studyinterestlevel::ad))